



**PROFESSIONAL
 2X DISTANCE MARKING PAINT SPRAYS**

DESCRIPTION AND USES

Rust-Oleum® Professional 2X Distance Marking Paint Sprays are an aerosol coating packaged for use in an inverted position as a marking paint. Use for marking construction and excavation sites, underground utilities and for traffic safety. This product is not water soluble and withstands general weathering. These sprays are recommended for use with Rust-Oleum® #2393000 Marking Wand and feature fast dry and adhesion to concrete, blacktop, gravel, soil and grass.

APPEARANCE

Flat to semi-gloss finish (dependent on surface porosity).

PRODUCTS

SKU	Description
266574	Fluorescent Green
266575	Caution Blue
266577	High Visibility Yellow
266579	Fluorescent Orange
266590	Fluorescent Red-Orange
266591	Safety Red
266592	Fluorescent Pink
266593	White
266594	Clear

PACKAGING

15-ounce containers, 6 containers/carton

PAINTING CONDITIONS

Use when temperature is 40-90°F (4-32°C) and humidity is below 85% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Protect surrounding surfaces from overspray. Overspray can carry a significant distance.

PRODUCT APPLICATION

SURFACE PREPARATION

Remove excessive loose debris from the surface before application of the coating.

PRODUCT APPLICATION

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN**. Contact Rust-Oleum. Shake often during use. Hold can upright 6-8" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart. **Do not use near open flame.**

DRY & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 15 minutes and is fully dry in 8 hours.

CLEAN-UP

When finished spraying, clear spray valve by turning can upright and pushing spray button for 2-3 seconds. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve



TECHNICAL DATA

PROFESSIONAL 2X DISTANCE MARKING PAINT SPRAYS

PHYSICAL PROPERTIES

		2X DISTANCE MARKING PAINT SPRAYS
Resin Type		Modified Alkyd
Pigment Type		Varies with color
Solvents		Acetone, Aliphatic Hydrocarbons
Fill Weight		15 ounces
MIR		0.85 Max
Practical Coverage at Recommended DFT (assumes 15% material loss)		Up to 800 linear feet (243 meters) at 1.5 in wide (3.8 cm) Depending on surface porosity
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	15 minutes
	Fully Dry	8 hours
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877-385-8155
www.rustoleum.com

Form: GDH-61
Rev.: 053017