TRUSTED QUALITY SINCE 1921.

## **RUST-OLEUM®**



## SHIMMER **FINISH GOLD GLITTER**

GREAT FOR HOLIDAY. **HOME DÉCOR & MORE** 

**MULTI-SURFACE USE** 

INDOOR USE ONLY



Rust-Oleum® Glitter provides an intense sparkling finish for any craft or decorative project. Glitter provides a full coverage of radiant shimmer for many surfaces including: wood, metal, wicker, glass, ceramic, pottery. Styrofoam®\* paper, plastic and more. For added protection, top coat with the Rust-Oleum® Glitter Clear Sealer.

READ ALL DIRECTIONS FIRST BEFORE BEGINNING PROJECT.

Painting Conditions: Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 10°C and 32°C and humidity is below 60% to ensure proper drying. Avoid spraying in very windy, dusty conditions.

Preparation: Remove loose paint and rust with wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry. Cover surrounding area to protect from spray mist.

Priming: Use of a Rust-Oleum® primer provides superior adhesion and hiding and is especially recommended for bare wood and metal.

Painting: Tip: For best results, use a similar base coat colour to enhance the shimmering coverage prior to applying Rust-Oleum® Glitter. Shake can vigorously for one minute after mixing ball begins to rattle. Shake often during use. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum®, Hold can upright 30-35cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart.

Dry & Recoat Times; based on 21°C - 50% relative humidity. Allow more time at cooler temperatures. May recoat at anytime. Dries to the touch in 20 minutes and to handle in 1 hour. Fully dry in 24 hours.

Clean-up: When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean up wet paint with Xylol or mineral turps. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

Clogging: If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral turps. Do not stick pin or other object into the stem.

\*Styrofoam® is a trademark of the Dow Chemical company.

For further application instructions refer to the Technical Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz or www.rustoleum.co.za

MANUFACTURED BY: Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, Illinois 60061, USA. IMPORTED AND/OR DISTRIBUTED BY: AUSTRALIA: PH: 0800 787 865; email: technical@rustoleum.co.nz, www.rustoleum.co.nz; SOUTH AFRICA: Rust-Oleum South Africa PTY, LTD, PO Box 400 Randvaal 1873 Gauteng, South Africa, PH: (016) 365 5120, email: info@spraymate.co.za.



CAUTION KEEP OUT OF REACH OF CHILDREN. READ SAFETY DIRECTIONS BEFORE OPENING OR USING. FLAMMABLE

WARNING STATEMENTS: Extremely Flammable. Irritation to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

SAFETY DIRECTIONS: DO NOT SWALLOW. Use only in well ventilated areas. Avoid contact with skin, eves and inhalation of vapour, spray or mist. Wear protective gloves and clothing. Avoid contact with eyes.

General: In case of doubt, or when symptoms persist seek medical advice immediately. Never give anything by mouth to an unconscious

Inhalation: Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical attention for any breathing difficulty. Skin: Wash thoroughly with water and soap. Remove any contaminated clothing. Wash contaminated clothing before re-use. If irritation occurs consult a physician.

Eyes: In case of eye contact, rinse immediately with plenty of water for at least 15 minutes and seek medical advice

Ingestion: If swallowed do NOT induce vomiting. For advice, contact a Poisons Information Centre (Poison Centre Phone: AUS 13 11 26; NZ 0800 764 766: SA 086 155 5777) or a doctor immediately.

For further information refer to the Safety Data Sheet available at www.rustoleum.com.au or www.rustoleum.co.nz or www.rustoleum.co.za

PRESSURISED CONTAINER, PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C. DO NOT PIERCE OR BURN, EVEN AFTER USE, DO NOT SPRAY ON A NAKED FLAME OR ANY INCANDESCENT MATERIAL. KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING



347863 GOLD GLITTER



291a NET

©2018 Rust-Oleum Corporation Made in the USA 348136 1018