

POISON
KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING



MOULD STOP PRIMER

Kills Existing Mould, Mildew and Odour Causing Bacteria
Paint directly over existing mould, mildew, odour causing bacteria and any other fungal organisms

Binds to chalky surfaces, masonry & metal
 Great for use under wallcoverings
 Household Grade Disinfectant
 This contains 4,5-Dichloro-2-N-octyl-3(2H)-isothiazolone 1.23 g/L



BEFORE



AFTER

INTERIOR/EXTERIOR

Water-Base • White • Tintable

3.78 LITRES

ZINSSER® Mould Stop Primer is a water-based fungicidal protective coating that can be used to paint over and kill existing mould, mildew, moss, fungi, odour causing bacteria and any other fungal organisms. The Mould Stop Primer contains an antimicrobial to prevent the growth of mould, mildew and other fungal organisms on the paint film. Additional information is listed in the safety data sheet. The Mould Stop Primer also aides in covering residual microbiological and fungal stains. See Product Data and Safety Data Sheet before application at www.rustoleum.com.au.

The Mould Stop Primer is for use on non-porous interior and exterior, residential attics, basements, window frames, bathrooms, wall cavities, baseboards, sub-floors and table tops. Mould Stop Primer can be used with any topcoat.

DIRECTIONS FOR USE

Fix the source of any moisture problems prior to remediation. Do not attempt to salvage damaged or structurally unsound building materials. Consult a qualified professional to perform a thorough inspection and supply work specifications appropriate to the project.

Surface Preparation & Application: For applications that have existing wet, slimy, heavily soiled, gross filth, overgrowth or loose material on the substrate a pre-cleaning step is required. Physically or mechanically remove gross filth, heavily soiled, overgrowth or loose material before application and ensure the substrate is free of slime or excessive moisture to ensure long-term adhesion and product performance. If mould or mildew needs to be removed prior to application remove with a mildew remover and let dry. Eye, skin and respiratory protection is highly recommended. Patch surface irregularities with appropriate patching compounds.

The Mould Stop Primer is a ready to use product. Do not thin. Do not mix with detergents or other chemicals. Use undiluted. Mix thoroughly. Do not apply when air or surface temperature is below 10°C or when drying conditions are poor. Use adequate ventilation during application.

Use a brush, roller, or airless sprayer to apply. (Follow spray equipment manufacturer's instructions; for airless spraying use 0.17 tip at 2000 – 2500 P.S.I.) Coverage is dependant on substrate porosity and surface smoothness.

Dries to the touch in 30 minutes; can be recoated in 1 hour. Full adhesion and hardness develops in 7 days.

Mould, Mildew, Fungi, Moss and Odour Causing Bacteria Control: The Mould Stop Primer will kill existing mould, mildew and fungal organisms. Apply the Mould Stop Primer generously and uniformly, ensuring that the surface is completely coated. Allow to air dry.

TINTING: Can be tinted with up to 16mL of universal colourant per litre. Tinting the undercoat toward the colour of the topcoat helps it hide in one coat.

COVERAGE: 37 – 41 m² per litre. Coverage rates may vary depending on the surface smoothness.

LIMITATIONS: Not for application to floors or decks or to surfaces subject to immersion or prolonged contact with water.

CLEANUP: Clean all tools and drippings with warm soapy water before coating dries. Shelf Life: 5 years. STORE ABOVE 10°C, **KEEP PRODUCT FROM FREEZING.**



RUST-OLEUM AUSTRALIA PTY, LTD.
 Unit 12, 4 Southridge Street
 Eastern Creek, NSW 2766 Australia
 PH: 1 300 784 476
 email: sales@rustoleum.com.au
www.rustoleum.com.au

HAYDN BRUSH CO. LTD.
 PO Box 4325
 Christchurch, New Zealand
 PH: 64 3 347 7770
 email: mail@haydn.co.nz

© 2015 Rust-Oleum Corporation Made in USA 299569 0615

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal. Storage: Store in original, tightly closed containers below 30°C and above 10°C in a secure area inaccessible to children and away from food or feed. For Residential Use Container Handling: Nonrefillable container. Do not reuse or refill this container. Securely wrap original container in several layers of newspaper and allow container residues to dry before discarding or offering for recycling if available.

SAFETY DIRECTIONS: Keep out of reach of children. Keep container tightly closed when not in use. Do not ingest the product. Due to the product being a coating material, if ingested this product may present an aspiration hazard. Excessive exposure may result in mild irritation to the eye, skin or respiratory system. Use only in well ventilated areas. In case of insufficient ventilation, or if spraying the product, wear suitable respiratory and eye/face protection. Wear nitrile or neoprene gloves to avoid prolonged skin contact. Contains 4,5-Dichloro-2-N-octyl-3(2H)-isothiazolone 1.23 g/L. May produce an allergic reaction in sensitive individuals. People with pre-existing skin conditions, such as eczema or dermatitis, should take precautions so as not to exacerbate the condition. The product contains a glycol component with the skin annotation assigned to it; hence absorption through the skin may be a source of exposure. As for all chemical products, persons should not expose open wounds, cuts, abrasions or irritated skin to this material. The product is harmful to aquatic organisms. Avoid release to the environment.

FIRST AID: If swallowed, do NOT induce vomiting. For advice, contact a Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766) or a doctor. If a large quantity has been ingested or vomiting has occurred after ingestion seek medical advice immediately taking the container or Safety Data Sheet with you. If in eyes, hold eyelids apart and flush with copious amounts of running water and seek medical assistance if irritation develops or persists. If skin or hair contact occurs, remove contaminated clothing and wash skin and hair thoroughly with soap and water. If irritation develops or persists seek medical attention. If affected by inhalation of vapours, remove person to fresh air and seek medical assistance if irritation develops or persists.

For further information refer to the **Material Safety Data Sheet** available at www.rustoleum.com.au.

The following applies to New Zealand Residents Only: WARNING: This product will perform as claimed if applied strictly according to instructions. The directions apply to most applications, but may not cover special conditions, techniques and/or surfaces. If you have a question, check with your supplier or contact Haydn Brush Company, Christchurch NZ. Warranty is strictly limited to replacement or the refunded value of product actually used if such product proves defective.

Contact Details: Haydn Brush Company Ltd, PO Box: 4325, 2 Link Drive, Izone Business Park, Rolleston, 7675, Christchurch, New Zealand. P: +64 3 347 7770 E: mail@haydn.co.nz

282520 MOULD STOP PRIMER



299569